

WE GO THE DISTANCE FOR YOU



## Ruggedized Vault Tower Series

### New Product Info

The Ruggedized Vault series is a true on-line, double-conversion design with power factor correction. They are ideal for the most critical and sensitive applications where the best level of power protection is required in harsh environments. Connected equipment is immune to the slightest power fluctuations, spikes, surges, noise, extended under- and over-voltages, harmonics and frequency variations.

An extremely wide input voltage tolerance (up to +/- 40%) and an output voltage regulation of within +/- 2% make the Vault one of the most flexible and technologically-advanced UPS's on the market. Aside from the traditional Tower form-factor, they're also available in a short-depth, compact Rack-Tower configuration.

Features such as UPS & power-monitoring software, integral auto-bypass, various communication options, extended run-time capability, cold-start, advanced battery management and microprocessor control, are all standard. However, a host of unique features and options bring some exclusivity to the series. They include a High Efficiency & Free-run mode, an EPO (Emergency Power Off) port and load segmentation control.

The units also feature an interactive, multifunction LCD panel that not only displays various UPS and related parameters, but allows the user to check, test and change settings such as output voltage, input and bypass modes from the front panel while the unit is on line. External battery packs (EBP) allow for greater operating temperatures in extended backup-time applications.

Offering 700VA / 490W to 1,500VA / 1,050W capacity, the UPS features temperature-compensated charging to provide an operating temperature range from 23°F to 131°F (-5°C to +55°C). Additionally, the unit includes conformal coating on all electric components that resists corrosion in high humidity installations.

**\*Suitably rated batteries are required for extreme temperature.**



### Features & Benefits

- True on-line double conversion topology
- Wide operating temperature range
- True sine-wave output with less than 3% THD
- Output voltage regulation to within +/- 2%
- High Efficiency (HE) & Free-run mode
- RS-232 & USB communication interface
- Multi-function, interactive control panel
- Input PF correction, frequency & bypass mode
- "Cold Start" + 'Gen Set compatibility' mode
- Event counter & timer + Time delay relay
- Emergency power off circuit (EPO)

**Options:**

- SNMP / Webcard
- Power transfer switch (PTS) / Maintenance bypass
- Battery wire harness kit

# Tower Model Specifications

GENERAL			
Model Number	VTRN-0700-C1	VTRN-1000-C1	VTRN-1500-C1
Rated Capacity	700VA / 490W	1000VA / 700W	1500VA / 1050W
Technology	True on-line, double conversion topology with integral automatic bypass		
INPUT			
Phase	Single phase plus ground		
Bypass Voltage	96 – 138 VAC (user selectable)		
Input Voltage Range	60 / 70 / 80VAC – 144 VAC (60V @ 40%, 70V @ 70%, 80V @ 100% load)		
Frequency	50 / 60 Hz Auto sensing		
AC Frequency Range	45 – 65 Hz		
Input Current (120V)	5.8A	8.2A	12.4A
Input Power Factor	0.97		
OUTPUT			
Output Voltage	110 / 115 / 120/ 127 VAC		
Voltage Regulation	± 2%		
Voltage Distortion	< 5% THD with non-linear loads, < 3% THD with linear loads		
Frequency Regulation	± 0.25 Hz (while on battery or in free run mode)		
Dynamic Response	± 9 % max from 100% to 20 % or from 20% to 100 % linear load		
Overload Capacity	100 – 125% for 1 min, 125 – 150 % for 10 sec		
Efficiency	Greater than 93% (HE Mode), Greater than 88% (On-line Mode)		
Crest Factor	3 : 1		
PHYSICAL			
Input (AC) Connection	Fixed power cord (std) or Hardwire Terminals (optional)		
Output (AC) Connection	6 x NEMA 5-15R (std) or Hardwire Terminals (optional)		
Dimensions in /mm W x D x H	6 x 16.5 x 9.4 / 152 x 420 x 238		
Weight lbs / kg (net)	17 / 7.7	19 / 8.6	20 / 9
Operating Temperature Range	-5° C to +55° C / 23° F to 131° F		

Notes:

1. These units do not contain internal batteries. Contact support@marathon-power.com for run times with various external battery options.
2. An additional internal 5A Charger is included.

Please contact us for additional information or to discuss your application requirements.  
We welcome feedback about your specific OEM and custom needs.



**2538 E. 54th Street**  
**Huntington Park, CA 90255**  
**Office: 310-689-2328**  
**Fax: 310-689-2329**  
**sales@marathon-power.com**  
**info@marathon-power.com**  
**www.marathon-power.com**

Your local representative / distributor is