

### Tower Extended Battery Packs

Model Number	VTPB-0018-36	VTPB-0018-48	VTPB-0018-72	VTPB-0018-96
Capacity	1000VA   700W	1500VA   1050W	2000VA   1400W	3000VA   2100W
Input Connection	Fixed Power Cord with color-coded Anderson connector			
Output Connection	Panel mounted, color-coded Anderson connector			
Battery Type & Rating	Sealed, lead-acid 7Ah/12V			
Battery Quantity	6	8	12	16
Backup Time (full load)	Refer to Backup Times Table			
Recharge Time	<4 hours to 90 %			
Dimensions in / mm W x D x H	6 x 16.5 x 9.4 152 x 420 x 238	6 x 19.7 x 9.4 152 x 500 x 238	8.9 x 16.5 x 14.1 225 x 420 x 358	
Weight lbs. / kg	44.1 / 20	57.3 / 26	92.6 / 42	104.1 / 47.2

### 19" Rack Mount Models

Model Number	VRPB-0018-36	VRPB-0018-48	VRPB-0018-72	VRPB-0018-72
Capacity	1000VA   700W	1500VA   1050W	2000VA   1400W	3000VA   2100W
Input Connection	Fixed Power Cord with color-coded Anderson connector			
Output Connection	Panel mounted, color-coded Anderson connector			
Battery Type & Rating	Sealed, lead-acid 7Ah/12V			
Battery Quantity	6	8	12	12
Backup Time (full load)	Refer to Backup Times Table			
Recharge Time	<4 hours to 90 %			
Dimensions in / mm W x D x H	16.9 x 16.7 x 3.3 428 x 425 x 84	16.9 x 19.7 x 3.3 428 x 500 x 84	16.9 x 25 x 3.3 428 x 631 x 84	
Weight lbs. / kg	38 / 17.3	39.8 / 18.1	69.5 / 31.6	72.6 / 33

### Tower Extended Battery Packs

Model Number	VTPB-0007-240	VTPB-0009-240
Capacity	6000VA   5400W	10000VA   9000W
Input Connection	Fixed Power Cord with color-coded Anderson connector	
Output Connection	Panel mounted, color-coded Anderson connector	
Battery Type & Rating	Sealed, lead-acid 7Ah/12V	Sealed, lead-acid 9Ah/12V
Battery Quantity	40	40
Backup Time (full load)	Refer to Backup Times Table	
Recharge Time	<4 hours to 90 %	
Dimensions in / mm W x D x H	10.1 x 23.2 x 22.4 257 x 590 x 570	10.1 x 27.1 x 23 257 x 690 x 585
Weight lbs. / kg	190 / 86	212.7 / 96.5

### 19" Rack Mount Models

Model Number	VRPB-0007-240	VRPB-0009-240
Capacity	6000VA   5400W	10000VA   9000W
Input Connection	Fixed Power Cord with color-coded Anderson connector	
Output Connection	Panel mounted, color-coded Anderson connector	
Battery Type & Rating	Sealed, lead-acid 7Ah/12V	Sealed, lead-acid 9Ah/12V
Battery Quantity	20	20
Backup Time (full load)	Refer to Backup Times Table	
Recharge Time	<4 hours to 90 %	
Dimensions in / mm W x D x H	16.9 x 23.5 x 5.1 428 x 597 x 130	16.9 x 25.9 x 5.1 428 x 657 x 130
Weight lbs. / kg	146 / 66	150 / 68