

Engineering Specifications

Model	AVRI-1000-02	AVRN-1000-01	AVRS-1000-02	AVRS-1500-02
Capacity	1000VA / 1000W	1000VA / 1000W	1000VA / 1000W	1500VA / 1500W
Phase	Single Phase			
AC Input				
Frequency	50Hz or 60Hz			
Voltage	1ϕ 2W			
Range	110 / 120 VAC ± 15% 220 / 230 / 240 VAC ± 15%			
AC Output				
Voltage	1ϕ 2W			
Voltage Regulation	110 / 120 VAC ± 5% (Typical) 220 / 230 / 240 VAC ± 5% (Typical)			
Frequency	50 Hz / 60 Hz Following Input			
Efficiency	> 95 %			
Protection				
Full Protection	Overload, Short Circuit, Surge			
Tel Communication	RJ11 / RJ45			
Management & Communication				
Indicator	LED Panel			
Physical				
Dimension (WxDxH) (in/mm)	4.84 in x 5.35 in x 4.02 in 123 mm x 136 mm x 102 mm			
Weight (lbs/kgs)	3.2 lbs / 1.4 kg	3.53 lbs / 1.6 kg	3.97 lbs / 1.8 kg	4.63 lbs / 2.1 kg
Shipping Dimension (WxDxH) (ins/mm)	5.71 in x 7.68 in x 4.72 in 145 mm x 195 mm x 120 mm			
Shipping Weight (lbs/kgs)	3.64 lbs / 1.65 kg	3.97 lbs / 1.8 kg	4.41 lbs / 2 kg	5.07 lbs / 2.3 kg
Environment				
Operating Humidity	0-95 % RH at 32-104°F / 0-40°C (Non-condensing)			
Audible Noise	Less than 40 dB			